

Date of print: 25.09.2009
 Date of last alteration: 25.09.2009 - Version 1.0 : english
 Art.-Nr., product name: **8050 VISKOFLEX**



1. Identification of the substance / preparation and of the company / undertaking

- 1.1 Identification of the substance or preparation:
- 1.1.1 Commercial Product Name: VISKOFLEX
- 1.2 Application of substance/preparation: commercial
Impression material for dental use
- 1.3 Company / undertaking identification:
- Manufacturer / distributor: Kohdent Roland Kohler Medizintechnik GmbH & Co. KG
 Street / POB-No.: Bodenseeallee 14-16
 State / postal code / city: D-78333 Stockach
 Telephone: +49 7771 / 64999-0 Telefax: +49 7771 / 64999-50
 E-Mail: info@kohler-medizintechnik.de
- 1.4 Emergency telephone: +49 7771 / 64999-0
 This number is busy only to office hours
 (Mo.- Do 7.00 – 17.30, Fr. 7.00 – 12.30)

2. Hazards identification

- 2.1 Classification: The product is not dangerous preparation in the sense of the guideline 1999/45/EG.
- 2.2 Critical hazards to man and environment: No special hazards

3. Composition / information on ingredients

- 3.1 Chemical characterisation (preparation): Contains Polydimethylsiloxan and fillers and pigment.
- 3.2 Hazards ingredient: None

4. First aid measures

- 4.1 General information: With accident or indisposition take to medical advice (if possible, label or SDB present).
- 4.2 After inhalation: provide fresh air
- 4.3 After contact with the skin: Products with cloth or paper mechanically remove. Wash off with much water and soap. With visible skin change or complaints take to medical advice (if possible, label or SDB present).
- 4.4 After contact with the eyes: Eyes with opened eyelid gap immediately 15 minutes with flowing water rinse out. Optician consult.
- 4.5 After swallowing: Rinse mouth out immediately and plentifully water in small portions after-drink. No vomiting cause. Take to medical advice with illness.
- 4.6 Self protection of the first-aid: To self protection pay attention (hand guard, foil masks („Life keys“).

Date of print: 25.09.2009
 Date of last alteration: 25.09.2009 - Version 1.0 : english
 Art.-Nr., product name: **8050 VISKOFLEX**



5. Fire fighting measures

- | | | |
|-----|--|--|
| 5.1 | Suitable extinguishing media: | Water mist, dry powder, foam, carbon dioxide |
| 5.2 | Extinguishing media which must not be used for safety reasons: | Jet of water |
| 5.3 | Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases: | No special hazards |
| 5.4 | Special protective equipment for fire fighting: | Use self-contained breathing apparatus |

6. Accidental release measures:

- | | | |
|-----|----------------------------|--|
| 6.1 | Personal precautions: | If material were set free, on slip hazard to make attentive. By buried material do not run. |
| 6.2 | Environmental precautions: | Do not leave waste water and into the ground in waters, to arrive. Local official regulations consider. |
| 6.3 | Methods for cleaning up: | Take up mechanically or with liquid-binding material (sand, kieselguhr, sawdust); To disposal see point 13 |

7. Handling and storage:

- | | | |
|-----|---|--|
| 7.1 | Handling:
Handling procedures:

Recommendation for fire and explosion protection: | The precautionary measures usual while handling chemicals are to be considered. With the use do not eat, drink or smoke.

General rules of the preventive fire protection consider. |
| 7.2 | Storage:
technical measures and storage conditions:
Requirements at storerooms and containers:
Requirements for storage with other products:
Additional storage conditions: | Store drying separately in closely closed original bundles coolly and from food.
Provide to good room ventilation.
No incompatible materials admits

Keep at temperature not exceeding 25°C / 77 °F.
Protect for moisture |
| 7.3 | Specified use: | Component B of an isolation mass on silicone basis for the oral dental cast; to the use by trained technical personnel |

Date of print: 25.09.2009
 Date of last alteration: 25.09.2009 - Version 1.0 : english
 Art.-Nr., product name: **8050 VISKOFLEX**



8. Exposure controls / personal protection

- 8.1 exposure limit values No assigned materials with workstation-furnished, to supervising limit values.
- 8.2 Components with limits of values:
- 8.2.1 Components with limits of values to be supervised at the workplace:
- General protection and hygiene measures: General hygiene measures while handling chemical materials consider. Do not eat with the work and drink.
- Personal protective equipment:
- Respiration: Not necessarily
- Hands: Recommended, e.g. Protective gloves from nitrile rubber.
- Eyes: Eye protector for the avoidance of mechanical injuries at the eye recommended.
- Personal: Work clothes wearing
- 8.2.2 Delimitation and monitoring of the environmental exposition: In waters and into the ground to arrive do not leave.

9. Physical and chemical properties

- 9.1 Appearance
- Form: Paste
- Colour: beige
- Odour: odourless
- 9.2 Important information to the health and environmental protection as well as for security Method (67/548/EWG)
- Flashpoint: = > 100 °C / 212 °F DIN 51755
- Ignition temperature: = > 200 °C / 392 °F DIN 51794
- Oxidizing properties: n.a.
- Explosive properties: n.a.
- Vapour pressure: = < 1 hPa bei 20 °C / 68 °F DIN 51757
- Density: = ca. 1,47 g/cm³ bei 20 °C / 68 °F
- Solubility in water: = virtually insoluble
- pH-value: n.a.
- Distribution coefficient octanol / water: n.a.
- Viscosity (dynamic): = ca. 10 Mio. mPa-s bei 23 °C / 73 °F Brookfield
- 9.3 Further information: Thermal decomposition: = > 250 °C / 482 °F

10 Stability and reactivity

- 10.1 Incompatibility with other Temperature > 150 °C / 302 °F (siehe 10.3).

Date of print: 25.09.2009
 Date of last alteration: 25.09.2009 - Version 1.0 : english
 Art.-Nr., product name: **8050 VISKOFLEX**



substances:
 10.2 Avoiding materials No noted.
 10.3 Hazardous decomposition products: In presence of air small quantities formaldehyde can be formed at temperatures starting from approx. 150 degrees / 302 °F by oxidative dismantling

11 Toxicological information

11.1 General information To handle after past knowledge while appropriate handling and considering the usual industrial hygiene without health dangers. After the conditions of our present knowledge neither mutagen, carcinogenically still teratogen.
 11.2 Toxicological Test
 Acute toxicity:
 Acute orale toxicity: For the product no toxicological data are present. For products of similar composition a LD₅₀ (oral, rat) was found of over 5 000 mg/kg

12. Ecological information

12.1 Ökotoxizität:
 Behavior in sewage plants (bacteria toxicity: Breathing/increase inhibition) To expect after present experience no unfavorable effects in sewage plants.
 12.2 Mobilität: Forms on the water surface a thin oil film. By suspended particles one absorbs. Separation by sedimentation.
 12.3 Persistence and degradableness
 Biological attack/ further information: Biologically not degradably. Polydimethylsiloxane are degradable by abiotische procedures to certain extent.
 12.4 Bio accumulation potential: Bio accumulation improbably
 12.5 Other harmful effects: none admits
 12.6 Further ökologische behavior: In the case of appropriate handling and use no environmental problems are to be expected.

13 Disposal consideration

13.1 Disposal/waste (product): Recommendation: Correct removal by burning in a special refuse combustion plant. Local official regulations are to be considered.
 EAK/AWV-waste-keyl: 07 02 17 (wastes from HZVA von Kunststoffen, synthetic rubber and artificial fibers; silicone type wastes, others than in 07 02 16 specified)
 13.2 Uncleaned packaging: Recommendation: Packing is completely to empty (drip-free, putty clean). Packing is under attention that valid in each case local/national regulations prefers supplying to a re-use and/or an utilization.

14 Transport

Date of print: 25.09.2009
 Date of last alteration: 25.09.2009 - Version 1.0 : english
 Art.-Nr., product name: **8050 VISKOFLEX**



Information

- 14.1 Land transport ADR/RID and GGVS/GGVE (Germany):
 GGVS/GGVE class: Not classified as hazardous goods.
 ADR/RID class:
 Warning sign – hazard no. :
 Identification product:
 Notice:
 Shipping symbol:
 LQ
- 14.2 Binnenschifftransport ADN/ADNR:
 Note: Not classified as hazardous goods.
- 14.3 Sea transport IMDG/GGVSee: IMDG/GGVSee-class; EmS-No. Not classified as hazardous goods..
 Marine pollutant:
 Proper shipping Name
 Technical name:
 LTD. QTY:
- 14.4 Air transport ICAO-TI and IATA-DGR:
 ICAO/IATA-class: Not classified as hazardous goods..
 Proper shipping name:
 Technical name:
 Notice:
 Air post: permitted

15 Regulatory information:

- 15.1 Classification according to EEC-guidelines: According to the Regulations for Hazardous Goods and the corresponding EC-Guidelines the product is not to be labelled.
- 15.2 National Prescription (Germany)
 Water hazard class: WGK 1 = weakly water-endangering (classification in accordance with appendix 4 VwVwS of 17.05.1999 in the current version).

16 Other information

- 16.1 Wording of the R-sentences under section 3: none
- 16.2 Further Information:
 Explanation of the abbreviations: n.a. = not applicable n.u. = not subject to:

Date of print: 25.09.2009
Date of last alteration:: 25.09.2009 - Version 1.0 : english
Art.-Nr., product name: **8050 VISKOFLEX**



16.3 Data original:

Characteristic data in terms of safety of chemical materials, exomed publishing house, collection of sheets with auxiliary supplies.

Manual of the refuse disposal, ecomed publishing house, collection of sheets with auxiliary supplies General administrative regulation for the change of the administrative regulation of water-endangering materials - VwVwS from 27 July of 2005.

Safety data sheets and further data of suppliers/manufacturers.

Data the given the product describe excluding the safety requirements of the Product/the products and support themselves on the today's conditions of our knowledge. They do not represent a warranty of characteristics of the descriptive product/the descriptive products in the sense of the legal guarantee regulations.